




**Data Sets (No. of Sensors)**

Metal Loss	216
Residual	108
Caliper	54
Odometer	2

**Physical Attributes**

Length	61 in (1549 mm)
Weight	517 lb (235 kg)



**Operational**

Maximum Pressure	1500 psi (10342 kPa)
Temperature Range	32° to 140°F (0° to 60°C)
<sup>1</sup> Velocity (Preferred)	0.1 to 9 mph (0.04 to 4 m/s)
Minimum Required Diff. Pressure (Launching)	45 psi (310 kPa)
Minimum Required Diff. Pressure (Running)	40 psi (276 kPa)

**Pipeline Geometry Requirements**

Local Min. Cross Section Diameter	12.80 in (325 mm)
Feature Bore Restriction Diameter	14.25 in (362 mm)
Minimum Bend Radius	1.5D
Minimum Bend Separation (1.5D Bends)	8 in (203 mm)
Minimum Tee Separation (Centerline to Centerline)	34 in (864 mm)
Maximum Recordable Wall Thickness [ @ 9 mph (4 m/s) ]	0.75 in (19 mm)

**Reporting**


<b>Metal Loss</b>	Refer to Tool Performance Specification
<b>Geometry Data</b>	
Reporting Threshold	0.5% of Pipe OD (0.08 in/2.0 mm)
Sizing Accuracy (Depth)	0.08 in (2.0 mm)
<b>Location Accuracy</b>	
Axial	±1 in (25 mm) within a joint
Circumferential	±10°
<b>Bend Data</b>	
Angle Accuracy	±2°

**Suggested Minimum Trap Dimensions**

Traps	A	B	C	D	E	F	G	H
<b>Launcher</b>	73 in (1854 mm)	31 in (787 mm)	18 in (457 mm)	18 in (457 mm)	64 in (1626 mm)	133 in (3378 mm)	16 in (406 mm)	4 in (102 mm)
<b>Receiver</b>	73 in (1854 mm)	73 in (1854 mm)	18 in (457 mm)	18 in (457 mm)	64 in (1626 mm)	133 in (3378 mm)	16 in (406 mm)	4 in (102 mm)

**Notes**

- Data quality and run success is dependent on tool speed & line conditions
- Pipelines that are outside of the scope of these specifications can be assessed on an individual basis
- Tool design may vary from image above
- <sup>1</sup>Optional Dynamic Speed Control available
- <sup>2</sup>Contact Enduro for details



**16" DfL-DD**