




Data Sets (No. of Sensors)

Physical Attributes

Caliper	24
Odometer	2

Length	66 in (1677 mm)
Weight	958 lb (435 kg)



Operational

Maximum Pressure	1500 psi (10342 kPa)
Temperature Range	32° to 140°F (0° to 60°C)
Velocity (Preferred)	0.1 to 9 mph (0.04 to 4 m/s)
Minimum Required Diff. Pressure (Launching)	20 psi (138 kPa)
Minimum Required Diff. Pressure (Running)	15 psi (103 kPa)

Pipeline Geometry Requirements

Minimum Cross Section Diameter	25.50 in (648 mm)
Minimum Bend Radius	1.5D
Minimum Bend Separation (1.5D Bends)	Back to Back
Minimum Tee Separation (Centerline to Centerline)	85 in (2159 mm)

Reporting


Dent/Ovality Sizing	
Dent Depth Sizing	0.17 in (4.3 mm)
Ovality ID Reduction Accuracy	0.17 in (4.3 mm)
Location Accuracy	
Feature to Upstream Girth Weld	±1 in (25 mm)
Feature Orientation	±15°
Bend Data	
Angle Accuracy	±2°
Axial Sampling	
Depends on Speed, Line Condition & Length 0.1 in (2.5 mm)	

Suggested Minimum Trap Dimensions (Contact Enduro For Minimum DdL-Combo Trap Dimensions)

Traps	A	B	C	D	E	F	G	H
Launcher	78 in (1981 mm)	33 in (838 mm)	18 in (457 mm)	36 in (914 mm)	82 in (2083 mm)	138 in (3505 mm)	34 in (864 mm)	10 in (254 mm)
Receiver	78 in (1981 mm)	78 in (1981 mm)	18 in (457 mm)	36 in (914 mm)	82 in (2083 mm)	138 in (3505 mm)	34 in (864 mm)	10 in (254 mm)

Notes

- Data quality and run success is dependent on tool speed & line conditions
- Pipelines that are outside of the scope of these specifications can be assessed on an individual basis
- Tool design may vary from image above
- ²Contact Enduro for details



34" DdL